


**COMPATIBLE WITH**

- ▶ Remote control weapon systems
- ▶ Camera tracking systems
- ▶ Gimbal systems
- ▶ Radar systems
- ▶ Rotator systems
- ▶ Turret systems
- ▶ Vehicle cabin/body systems
- ▶ Aircraft cabin systems


**FACTS**

- ▶ 6 degrees of freedom
- ▶ 6 electro-mechanical actuators
- ▶ 500 kg total payload
- ▶ 300 mm actuator stroke


**APPLICATIONS**

- ▶ Turret & RCW test
- ▶ Component validation
- ▶ Signal replication
- ▶ Signal generation
- ▶ Real time simulation table
- ▶ Field data system testing simulator

**3D CONNECTION CONTROLLER  
OPTIONAL**

**SMOTION PRODUCT LINE**

SMOTION50

SMOTION100

SMOTION200

**SMOTION500**

SMOTION800


SMOTION1000


**DIMENSIONS**

 L 1.6 X<sub>w</sub> 1.4 X<sub>h</sub> 1.2 m




### TECHNICAL SPECIFICATIONS



### HARDWARE COMPONENTS

- ▶ User friendly interface control (GUI)
- ▶ Hardware real-time control
- ▶ UDP based PC communication
- ▶ IMU integrated measurement system
- ▶ Passive and active limitations

### Performance Specifications

▶ Gross Moving Load up to	<b>500 kg</b>
▶ Actuator Stroke	<b>300 mm</b>
▶ Center of Gravity Above Top Platform	<b>0.50 m (Max)</b>
▶ Settled Height	<b>0.80 m</b>
▶ Neutral Height	<b>1.10 m</b>

### Moment of Inertia About

▶ Moment of Inertia About X axis	<b>250 kg.m<sup>2</sup></b>
▶ Moment of Inertia About Y axis	<b>250 kg.m<sup>2</sup></b>
▶ Moment of Inertia About Z axis	<b>250 kg.m<sup>2</sup></b>

### Power Supply

- ▶ 380VAC ±10%, 3ph , 50/60Hz

### Velocity

Surge ± 0.45 m/s ± 5 m/s<sup>2</sup>

Sway ± 0.45 m/s ± 5 m/s<sup>2</sup>

Heave ± 0.35 m/s ± 6 m/s<sup>2</sup>

Roll ± 40°/s ± 300°/s<sup>2</sup>

Pitch ± 40°/s ± 300°/s<sup>2</sup>

Yaw ± 50°/s ± 500°/s<sup>2</sup>

### Acceleration

Surge ± 5 m/s<sup>2</sup>

Sway ± 5 m/s<sup>2</sup>

Heave ± 6 m/s<sup>2</sup>

Roll ± 300°/s<sup>2</sup>

Pitch ± 300°/s<sup>2</sup>

Yaw ± 500°/s<sup>2</sup>

### Excursion

Surge -0.22 m - 0.24 m -0.30 m - 0.30 m

Sway -0.22 m - 0.22 m -0.31 m - 0.31 m

Heave -0.19 m - 0.18 m -0.19 m - 0.18 m

Roll -21.00° - 21.00° -24.00° - 24.00°

Pitch -20.00° - 22.00° -25.00° - 25.00°

Yaw -22.00° - 22.00° -26.00° - 26.00°

### Single Axis

Surge -0.22 m - 0.24 m -0.30 m - 0.30 m

Sway -0.22 m - 0.22 m -0.31 m - 0.31 m

Heave -0.19 m - 0.18 m -0.19 m - 0.18 m

Roll -21.00° - 21.00° -24.00° - 24.00°

Pitch -20.00° - 22.00° -25.00° - 25.00°

Yaw -22.00° - 22.00° -26.00° - 26.00°

### Multi Axis

Surge -0.22 m - 0.24 m -0.30 m - 0.30 m

Sway -0.22 m - 0.22 m -0.31 m - 0.31 m

Heave -0.19 m - 0.18 m -0.19 m - 0.18 m

Roll -21.00° - 21.00° -24.00° - 24.00°

Pitch -20.00° - 22.00° -25.00° - 25.00°

Yaw -22.00° - 22.00° -26.00° - 26.00°



### SIMPLE, SAFE AND ERGONOMIC SOFTWARE

- ▶ Signal generations
- ▶ Field data signal replication
- ▶ Real time signal visualization
- ▶ Signal recording and processing

### USER FRIENDLY GUI

